



10/525759
PCT/GB 2003 / 003454
Rec'd PCT/PTO 28 FEB 2005

INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road

Newport REC'D 25 SEP 2003
South Wales
NP10 8QQ PO PCT

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


BEST AVAILABLE COPY

Signed

Stephen Hordley

Dated 12 September 2003

Patents Form 1/77

Patents Act 1977
(Rule 16)

The
Patent
Office

16AUG02 E741736-2 D00016
P01/7700 0.00-0219139.3

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form.)

1. Your reference

DB/DEP02392/BEP

2. Patent application number

(The Patent Office will fill in this part)

0219139.3

16 AUG 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Designiche Limited
Archer House
Britland Industrial Estate
Northbourne Road
Eastbourne
East Sussex BN22 8PW
United Kingdom

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

844 6965001

4. Title of the invention

BARRIER SYSTEM

5. Name of your agent (if you have one)

BROOKES BATCHELLOR

"Address for service" in the United Kingdom, to which all correspondence should be sent (including the postcode)

102-108 CLERKENWELL ROAD
LONDON
EC1M 5SA

Patents ADP number (if you know it)

08142291001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

YES

a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.
See note (d))

Patents Form 1/77

0044662 16-AUG-02 04:50

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form —

Description 4

Claim(s) 2

Abstract —

Drawing(s) 1

10. If you are also filing any of the following, state how many against each item.

Priority documents —

Translations of priority documents —

Statement of inventorship and right to grant of a patent (Patents Form 7/77) —

Request for preliminary examination and search (Patents Form 9/77) —

Request for substantive examination (Patents Form 10/77) —

Any other documents (please specify) —

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

Brookes Batchelor 16/8/02

12. Name and daytime telephone number of person to contact in the United Kingdom

DAVID BAILEY

01892 510600

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Patents Form 1/77

BARRIER SYSTEM

5 The present invention relates to a barrier system, in particular to a barrier system of particular use in queuing situations, deterring entry of personnel into prohibited areas and for guiding flows of people.

10 A well-known system for directing queues involves a device including vertically supported post carrying at its upper end on one side therefore a length of webbing retractably mounted upon a tensioned reel. The free end of the webbing includes an attachment element which is adapted to be retained by a corresponding connecting element on the opposite side of the upper end of the post. By this arrangement, a plurality of such devices can be linked to form a barrier.

15 Such barriers are highly effective but are cumbersome. They are not well adapted for ease of movement. The present invention seeks to address this problem.

20 In its broadest sense, the present invention provides a barrier system comprising a main pillar and at least one demountable satellite pillar wherein each of said main and satellite pillars includes rolling means, such as wheels or castors, enabling the pillar to be moved easily along a surface. Each of the pillars is joined to an adjacent pillar by at least one retractable webbing assembly.

25 Preferably each pillar is joined to each adjacent pillar by two retractable webbing assemblies.

30 In one embodiment, each retractable webbing assembly comprises a length of webbing mounted at a first end thereof to a tensioned reel for retraction there into and mounted at a second end thereof to an attachment element adapted to be received and retained by a corresponding connecting element upon the adjacent pillar.

In an alternative embodiment, each retractable webbing assembly comprises a length of webbing mounted at a first end thereof to a first tensioned reel for retraction there into and at a second end thereof to a second tensioned reel for retraction there into; the first and second reels each being mounted upon a respective pillar.

5

Typically, the main pillar is connected to two satellite pillars. Any number of further satellite pillars may be attached to these satellite pillars in series.

10

The above and other aspects of the present invention will now be described in further detail, by way of example only, with reference to the accompanying figures in which:

Figure 1 is a perspective view of an embodiment of a barrier in accordance with the present invention in an expanded or operative configuration;

15

Figure 2 illustrates more closely the method of retaining the webbing in position in the embodiment of Figure 1;

Figure 3 illustrates a braking arrangement for the wheels of the embodiment of Figure 1; and

20

Figure 4 is a plan view of the embodiment of Figure 1 in a retracted or stowed configuration.

25

Referring to the figures, an embodiment of a barrier in accordance with the present invention may typically include a main pillar 10 and demountable first and second satellite pillars 11,12

30

In the embodiment shown, satellite pillars 11,12 are demountable by means of their each carrying a horizontal bar 13 receivable in a corresponding elongate cavity 14 provided in main pillar 10.

Main pillar 10 and each of the satellite pillars 11,12 includes a pair of wheels. As illustrated, main pillar 10 has a pair of wheels 20 mounted at respective ends of a common axle mounted on the frame of the pillar 10, whereas satellite pillars 11,12 have separate wheels 21,22 mounted independently. Alternative arrangements will be readily apparent to the skilled person, including the use of alternative rolling means such as castors.

Pillar wheels 20,21,22 are lockable to prevent their rotation and thus movement of the respective pillar once at the desired location. Suitably this is achieved by a simple brake mechanism of the kind typically found on a child's pram or buggy in which a bar 23 (Figure 3) or similar element is caused to bear down upon the rolling surface of the wheel (typically a deformable rubber composition) by means of the bar 23 being pivotally mounted upon a frame 24 and actuatable by means of a foot-operated pedal 25.

In the embodiment shown, each satellite pillar 11,12 is joined to the main pillar 10 by two lengths of webbing 30,31. The webbing may be mounted by any conventional means. In the embodiment shown, a first end of each length of webbing is mounted on a tensioned reel 34 in which the webbing is spring-biased into a retracted or non-extended configuration. A second end of the webbing is terminated in an attachment element 32 which is adapted to be received by a corresponding connecting element 32 which is adapted to be received by a corresponding connection element 33 mounted upon a respective pillar.

The specific mounting of the webbing is not essential and many suitable arrangements will be apparent to the skilled person. In the embodiment shown, each tensioned reel 34 of the webbing assemblies whereby the main pillar 10 is joined to adjacent satellite pillars 11,12 is mounted a main pillar 10. Tensioned reel 34 could equally well be mounted upon each satellite pillar.

In an alternative embodiment, not shown, both ends of the webbing 30,31 are retractably mounted upon respective tensioned reels.

5 Suitably, the webbing is formed from a reflective material and may carry suitable wording by way of a notice, for example "KEEP OUT" or "STAND BACK" or arrows indicating a direction of movement. The webbing may also be connected to an alarm system activated, for example, upon contact with the webbing.

10 The barrier may also include illumination modules 40, powered by internal batteries or an external supply. One area where it is envisaged that the present barrier will find great use is as a mobile barrier for erecting adjacent to an aircraft when standing at an airport gate. The barrier can be used to direct passengers away from hazards such as the engines or the wings generally. Particularly for night-time use, the addition of illumination will be of great benefit.

15 It will be appreciated that any number of satellite pillars 11,12 may be connected in series to a central main pillar 10 to provide a barrier of substantially any length.

20 In the preferred embodiments, main pillar 10 includes, for additional support, small wheels or castors 41. Typically, there are mounted below a plate 42 of the pillar 10 which can also act as a support for supplementary articles depending upon the context in which the apparatus will be used, such as a fire extinguisher.

CLAIMS

1. A barrier system comprising a main pillar and at least one demountable satellite pillar; wherein each of said main and satellite pillars includes rotatable rolling means, said rolling means including locking means to prevent rotation of said rolling means; wherein each of said pillars is joined to an adjacent pillar by at least one respective retractable webbing assembly.
2. A barrier system as claimed in Claim 1 wherein the rolling means comprises a pair of wheels.
3. A barrier system as claimed in Claim 2 wherein the locking means comprise a brake assembly comprising a bar acting against the rolling surface of at least one of the wheels.
4. A barrier system as claimed in any one of Claims 1 to 3 wherein each pillar is joined to each adjacent pillar by two retractable webbing assemblies.
5. A barrier system as claimed in any one of Claims 1 to 4 wherein each retractable webbing assembly comprises a length of webbing mounted at a first end thereof to a tensioned reel for retraction there into and mounted at a second end thereof to an attachment element adapted to be received and retained by a corresponding connecting element upon the adjacent pillar.
6. A barrier system as claimed in any one of Claims 1 to 4 wherein each retractable webbing assembly comprises a length of webbing mounted at a first end thereof to a first tensioned reel for retraction there into and at a second end thereof to a second tensioned reel for retraction there into; the first and second reels each being mounted upon a respective pillar.

6

7. A barrier system as claimed in any one of Claims 1 to 6 comprising a further satellite pillar demountably carried by at least one of said satellite pillars.




FIGURE 2

WEBBING UNITS CAN BE LINKED AND ANGLED AS REQUIRED TO SUIT GUARDED AREA

FLASHING LIGHT UNITS: EXTERNAL SUPPLY VIA SOCKET, OR BATTERY MODULES






FIGURE 1



This Page is inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images
problems checked, please do not report the
problems to the IFW Image Problem Mailbox**